



1235 mm



880 mm





985 mm

## SPECIFICATIONS

	Recommended excavator	ton	7 - 11
	Weight	ton	0,72
	Load capacity	m <sup>3</sup>	0,35
	Pressure	bar	200 - 250
	Oil flow rate*	l/min.	75 - 100

\* The minimum hydraulic flow rate value must be alongside the required operating pressure.

## SHAFT KIT

KIT	ADJUSTMENT*	APPLICATION
 RQ8/RQ20/RQ50 Sifting kit	8/20/50 mm	Sifting damp/dry soil Soil aeration
 RM Mixer kit	-	Soil Aeration Compost Aeration Charcoal reduction Glass reduction Drywall reduction
 RQ8/RQ20/RQ50 Sifting kit	8/16 mm	Sifting damp/dry soil
 RC Compost kit	36,5 mm	Shredding foliage and small branches Composting

\* Shafts in closed position.

## ACCESSORIES

RQ8/RQ20/RQ50 Sifting kit	RM Mixer kit
RE8/RE16 Fine Sifting kit	RC Compost kit
Shaft holder	24 Month Warranty

## AREAS OF APPLICATION



ROAD WORKS



TUNNELS



ENCLOSED SPACES



PIPELINES

RECYCLING  
AGGREGATES

EXCAVATIONS

URBAN  
CONSTRUCTION SITES

FOUNDRIES

MAINTAINING  
LANDSCAPING AND  
AGRICULTURAL AREAS